

Stand 3.4.2020

Shaft	Spine	Length in Inch	Straightness	GPI	I/D in Inch	O/D in Inch (mm)	Protector Hat (mm)
Traditional Black	350	32"	.006	9.70	.245	.299 / 7,59	7.75
Traditional Black	400	32"	.006	9.20	.245	.296 / 7,51	7.75
Traditional Black	500	32"	.006	7.80	.245	.278 / 7,28	7.45
Traditional Black	600	32"	.006	6.80	.245	.285 / 7,23	7.30
Traditional Black	700	32"	.006	6.50	.245	.285 / 7,16	7.30
Traditional Black	800	32"	.006	6.10	.245	.285 / 7,08	7.30
Traditional Bamboo	350	32"	.006	10.27	.245	.301 / 7,64	7.90
Traditional Bamboo	400	32"	.006	9.36	.245	.300 / 7,62	7.90
Traditional Bamboo	500	32"	.006	8.26	.245	.293 / 7,44	7.75
Traditional Bamboo	600	32"	.006	7.26	.245	.291 / 7,39	7.60
Traditional Bamboo	700	32"	.006	6.96	.245	.289 / 7,34	7.45
Traditional Bamboo	800	32"	.006	6.56	.245	.284 / 7,21	7.30
Bandit	350	32"	n/a	8.00	.245	.293 / 7,45	7.60
Bandit	400	32"	n/a	7.30	.245	.288 / 7,33	7.45
Bandit	500	32"	n/a	7.00	.245	.287 / 7,31	7.30
Bandit	600	32"	n/a	5.80	.245	.280 / 7,13	7.30
Bandit	700	32"	n/a	4.90	.245	.274 / 6,97	7.15
Bandit	800	32"	n/a	4.50	.245	.272 / 6,92	7.00
Bandit	900	32"	n/a	4.20	.245	.271 / 6,89	6.90
Bandit	1000	32"	n/a	4.00	.245	.270 / 6,86	6.90
Timberstick	400	32"	.006	7.30	.245	.289 / 7,34	7.45
Timberstick	500	32"	.006	7.00	.245	.288 / 7,31	7.45
Timberstick	600	32"	.006	5.80	.245	.281 / 7,13	7.30
Timberstick	700	32"	.006	4.90	.245	.278 / 7,06	7.15
Timberstick	800	32"	.006	4.50	.245	.274 / 6,99	7.00
Timberstick	900	32"	.006	4.20	.245	.272 / 6,91	7.00
Hunter Extreme	300	32"	.003	10.67	.244	.309 / 7,87	7.90
Hunter Extreme	350	32"	.003	10.29	.244	.307 / 7,81	7.75
Hunter Extreme	400	32"	.003	9.62	.244	.303 / 7,70	7.75
Hunter Extreme	500	32"	.003	8.15	.244	.297 / 7,55	7.60
Hunter Extreme	600	32"	.003	6.57	.244	.287 / 7,29	7.30
Hunter Extreme	700	32"	.003	5.82	.244	.282 / 7,17	7.30
Hunter Extreme	800	32"	.003	5.44	.244	.280 / 7,12	7.15
Traditional Extreme	300	32"	.006	12.52	.244	.328 / 8,34	8.45
Traditional Extreme	350	32"	.006	12.00	.244	.325 / 8,26	8.30
Traditional Extreme	400	32"	.006	10.70	.244	.322 / 8,19	8.30
Traditional Extreme	500	32"	.006	10.10	.244	.318 / 8,10	8.15
Traditional Extreme	600	32"	.006	9.90	.244	.316 / 8,04	8.15
Heavy Hunter	320	32"	.006	14.27	.245	.324 / 8,22	8.45
Heavy Hunter	400	32"	.006	12.01	.245	.314 / 7,97	8.15
Heavy Hunter	500	32"	.006	11.55	.245	.312 / 7,92	8.00
Heavy Hunter	600	32"	.006	11.18	.245	.309 / 7,84	8.00

Shaft	Spine	Length in Inch	Straightness	GPI	I/D in Inch	O/D in Inch (mm)	Protector Hat (mm)
Slim Lines							
Slim Line Black	400	32"	.006	9.20	.175	.250 / 6,35	6.30
Slim Line Black	500	32"	.006	7.50	.175	.236 / 5,99	6.15
Slim Line Black	600	32"	.006	7.30	.175	.234 / 5,94	6.15
Slim Line Black	700	32"	.006	6.27	.175	.225 / 5,72	5.75
Slim Line Black	800	32"	.006	5.70	.175	.223 / 5,66	5.75
Slim Line Black	1000	32"	.006	5.00	.175	.218 / 5,53	5.60
Slim Line Black	1300	32"	.006	4.50	.175	.213 / 5,41	5.45
Slim Line Black	1600	32"	.006	4.10	.175	.209 / 5,30	5.45
Slim Line Timber	400	32"	.006	9.57	.175	.252 / 6,40	6.45
Slim Line Timber	500	32"	.006	7.97	.175	.239 / 6,07	6.15
Slim Line Timber	600	32"	.006	7.63	.175	.235 / 5,96	6.15
Slim Line Timber	800	32"	.006	6.05	.175	.225 / 5,71	5.90
Slim Line Timber	1000	32"	.006	5.34	.175	.218 / 5,53	5.75
Slim Line Timber	1300	32"	.006	4.87	.175	.215 / 5,46	5.60
Slim Line Timber	1600	32"	.006	4.49	.175	.213 / 5,41	5.60
Slim Line Bamboo	400	32"	.006	9.94	.175	.252 / 6,40	6.45
Slim Line Bamboo	500	32"	.006	7.99	.175	.238 / 6,04	6.15
Slim Line Bamboo	600	32"	.006	7.73	.175	.236 / 5,99	6.15
Slim Line Bamboo	800	32"	.006	6.11	.175	.225 / 5,71	5.90
Slim Line Bamboo	1000	32"	.006	5.42	.175	.220 / 5,58	5.75
Slim Line Bamboo	1300	32"	.006	4.99	.175	.215 / 5,46	5.60
Slim Line Bamboo	1600	32"	.006	4.61	.175	.211 / 5,35	5.60